



DATA SHEET FOR
TRANSFORMER # 704.222

Made for STANDARD

| LEADS | | SCHEMATIC | | | | LEADS | |
|---------|------|-----------|--|--|--------|---------------------|---------|
| S#22/8" | 0V | WHITE | | | BROWN | 0V | S#22/8" |
| S#22/8" | 117V | YELLOW | | | RED | 22V RMS / 0.75A RMS | S#22/8" |
| S#22/8" | 0V | ORANGE | | | ORANGE | 0V | S#22/8" |
| S#22/8" | 117V | BLACK | | | YELLOW | 22V RMS / 0.75A RMS | S#22/8" |

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/-10%
RATED PRIMARY CURRENT: 0.4/0.2A
RATED FREQUENCY: 50/60 Hz
TEMP. RISE AT RATED LOAD: 65°C

| | | |
|---------------------------|-----------------------|--------------------------|
| <u>DIMENSIONS/WEIGHT:</u> | <u>MOUNTING:</u> | <u>CORE DATA:</u> |
| OD = 2.8" | WASHER/PADS = 50mm | CORE # 30 |
| H = 1.3" | THICKNESS = 0.04" | CORE LOSS = 0.2 W |
| WEIGHT = 1.1BS. | HOLE DIAMETER = 0.17" | NO-LOAD CURRENT = 2.5 mA |

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label:



SPEC DATE: 09/20/18

(Logo)

Transformer # 704.222 (U2058)
Prim. 2x117V 50/60Hz bk(wh-ye/or-bk)
Sec. 2x22V / 0.75A br-re / or-ye
(date code)

By: *MX/LL*

(date code)

TOROID CORPORATION