

DATA SHEET FOR
TRANSFORMER # 713.222

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>
M#24/8"	0V	WHITE		BROWN	0V	M#18/8"
M#24/8"	117V	YELLOW		RED	22V RMS / 3.18A RMS	M#18/8"
M#24/8"	0V	ORANGE		ORANGE	0V	M#18/8"
M#24/8"	117V	BLACK		YELLOW	22V RMS / 3.18A RMS	M#18/8"


PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
LEADS: M=Magnet wire self-leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/-10%
RATED PRIMARY CURRENT: 1.4/0.7A
RATED FREQUENCY: 50/60 Hz
TEMP. RISE AT RATED LOAD: 61°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 3.9"	WASHER/PADS = 70mm	CORE # 900140
H = 1.9"	THICKNESS = 0.05"	CORE LOSS = 0.9 W
WEIGHT = 3.0 LBS.	HOLE DIAMETER = 0.25"	NO-LOAD CURRENT = 8.7 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label:  Transformer # 713.222 (U2079)
 SPEC DATE: 09/20/18 PRI. 2x117V 50/60Hz BK (WH-YE/OR-BK)
 (Logo) SEC. 2x22V/3.18A BR-BR/OR-YE
 By: *mx* (date code)

TOROID CORPORATION