



DATA SHEET FOR
TRANSFORMER # 713.302

Made for STANDARD

LEADS		SCHEMATIC				LEADS	
M#24/8"	0V	WHITE		BROWN	0V	M#20/8"	
M#24/8"	117V	YELLOW		RED	30V RMS / 2.33A RMS	M#20/8"	
M#24/8"	0V	ORANGE		ORANGE	0V	M#20/8"	
M#24/8"	117V	BLACK		YELLOW	30V RMS / 2.33A RMS	M#20/8"	

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
LEADS: M=Magnet wire self leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/-10%
RATED PRIMARY CURRENT: 1.4/0.7A
RATED FREQUENCY: 50/60 Hz
TEMP. RISE AT RATED LOAD: 65°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 3.9"	WASHER/PADS = 70mm	CORE # 900140
H = 1.9"	THICKNESS = 0.05"	CORE LOSS = 0.9 W
WEIGHT = 3.0 LBS.	HOLE DIAMETER = 0.25"	NO-LOAD CURRENT = 8.7 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. RoHS compliant.

Label:



SPEC DATE: 09/20/18

(Logo)

Transformer # 713.302 (U2082)
Prim. 2x117V 50/60Hz bk(wh-ye/or-bk)
Sec. 2x30V / 2.33A br-re / or-ye
(date code)

(date code)

By: *MX / LL*

TOROID CORPORATION