



DATA SHEET FOR
TRANSFORMER # 910.1201

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>	
S#16/12"	0V	WHITE		S#14/12"	
S#16/12"	100V	BLUE		WHITE 0V	
S#16/12"	120V	YELLOW		A/R THERMAL FUSE 120°C	
S#16/12"	0V	ORANGE		UO = 124.5V RMS	S#14/12"
S#16/12"	100V	RED		120V RMS / 1000VA	
S#16/12"	120V	BLACK		VIOLET 0V	S#18/12"

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
RATED PRIMARY CURRENT: 10.5/8.7/4.8/4.4A
RATED FREQUENCY: 50/60 Hz
TEMP. RISE AT RATED LOAD: 58°C

DIMENSIONS/WEIGHT:
OD = 6.6"
H = 3.7"
WEIGHT = 17.2 LBS.

MOUNTING:
SPECIFIED BY CUSTOMER

CORE DATA:
CORE # 1200
NO-LOAD LOSS = 5.3 W
NO-LOAD AMPS = 48 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, AAMI ES60601.1, CUL certified to CSA C22.2 No. 60601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label:



SPEC DATE: 09/19/16

Transformer # B04316196 (910.1201)
Input Volt: 100/120/200/220/240V
Input Current: 11/9/6/5/5A

(Logo)

By: **MX**

(date code)

TOROID CORPORATION