



DATA SHEET FOR  
TRANSFORMER # 915.1202

Made for STANDARD

LEADS		SCHEMATIC		LEADS			
S#14/12"	0V	WHITE		BROWN	0V	S#16/12"	
S#14/12"	100V	BLUE		A/R THERMAL FUSE 120°C			
S#14/12"	120V	YELLOW		UO = 124.5V RMS	RED	120V RMS / 750VA	S#16/12"
S#14/12"	0V	ORANGE			ORANGE	0V	S#16/12"
S#14/12"	100V	RED		A/R THERMAL FUSE 120°C	YELLOW	120V RMS / 750VA	S#16/12"
S#14/12"	120V	BLACK			VIOLET	STATIC SHIELD	S#18/12"

PRIMARIES ARE INSIDE A SLEEVE.  
Primaries must be connected together in series or in parallel.  
LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%  
RATED PRIMARY CURRENT: 15.7/13.0/7.1/6.5A  
RATED FREQUENCY: 50/60 Hz  
TEMP. RISE AT RATED LOAD: 60°C

DIMENSIONS/WEIGHT:  
OD = 9.0"  
H = 3.7"  
WEIGHT = 24.2 LBS.

MOUNTING:  
SPECIFIED BY CUSTOMER

CORE DATA:  
CORE # 1700  
NO-LOAD LOSS = 6.7 W  
NO-LOAD AMPS = 59 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer meets UL recognized UL 2601-1, AAMI ES60601-1, CUL certified to CSA C22.2 No. 60601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label:



Transformer # B04313353 (915.1202)  
Input Volt: 100/120/200/220/240V  
Input Current: 16/13/8/8/7A

SPEC DATE: 09/19/16

(Logo)

By: **MX**

(date code)

TOROID CORPORATION