



DATA SHEET FOR  
AUTO-TRANSFORMER # A5615

Made for STANDARD

LEADS

SCHEMATIC

LEADS

S#22/8"	COMMON	WHITE	
S#22/8"	120V input	BLACK	
S#22/8"	230V/250VA	BROWN	

LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

-----

NOMINAL SUPPLY: 120V +/-10%  
 RATED PRIMARY CURRENT: 2.2A  
 RATED FREQUENCY: 60 Hz  
 TEMP. RISE AT RATED LOAD: 45 °C


DIMENSIONS/WEIGHT:  
 OD = 3.9"  
 H = 1.7"  
 WEIGHT = 2.6 LBS.

MOUNTING:  
 WASHER/PADS = 70mm  
 THICKNESS = 0.05"  
 HOLE DIAMETER = 0.25"

CORE DATA:  
 CORE # 900115  
 CORE LOSS = 0.7 W  
 NO-LOAD CURRENT = 15 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506 and CUL certified to CSA C22.2 No. 66 standards. Class B insulation. RoHS compliant.

Label:  Auto-Transformer # A5615  
 Input: 120Vac 60Hz blk-wht  
 Output: 230V 250VA brn-wht

By: **MX** (date code)

SPEC DATE: 06/18/15 (Logo)

**TOROID CORPORATION**