



DATA SHEET FOR
AUTO-TRANSFORMER # A5618

Made for STANDARD

LEADS

SCHEMATIC

LEADS

S#16/8"	COMMON	WHITE	
S#16/8"	120V input	BLACK	
S#16/8"	230V/1000VA	BROWN	

LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120V +/-10%
RATED PRIMARY CURRENT: 8.7A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 63 °C

DIMENSIONS/WEIGHT:

OD = 5.5"
H = 2.3"
WEIGHT = 7.1 LBS.

MOUNTING:

WASHER/PADS = 110mm
THICKNESS = 0.08"
HOLE DIAMETER = 0.32"

CORE DATA:

CORE # 900491
CORE LOSS = 2.0 W
NO-LOAD CURRENT = 43 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506 and CUL certified to CSA C22.2 No. 66 standards. Class B insulation. RoHS compliant.

Label:



SPEC DATE: 06/18/15

(Logo)

Auto-Transformer # A5618
Input: 120Vac 60Hz blk-wht
Output: 230V 1000VA brn-wht

By: **MX**

(date code)

TOROID CORPORATION