



DATA SHEET FOR
AUTO-TRANSFORMER # A5621

Made for STANDARD

LEADS

SCHEMATIC

LEADS

S#18/8"	230V INPUT	BROWN	
S#18/8"	120V/500VA	BLACK	
S#18/8"	COMM.	WHITE	

LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 230V +/-10%
RATED PRIMARY CURRENT: 2.3A
RATED FREQUENCY: 50/60 Hz
TEMP. RISE AT RATED LOAD: 50 °C

DIMENSIONS/WEIGHT:

OD = 4.5"
H = 2.2"
WEIGHT = 4.8 LBS.

MOUNTING:

WASHER/PADS = 90mm
THICKNESS = 0.06"
HOLE DIAMETER = 0.25"

CORE DATA:

CORE # 900240
CORE LOSS = 1.3 W
NO-LOAD CURRENT = 13 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL506 and CUL certified to CSA C22.2, No. 66 standard. Class B insulation. RoHS compliant.

Label:



SPEC DATE: 06/18/15

Auto-Transformer # A5621
INPUT: 230VAC 50/60Hz BRN-WHT
OUTPUT: 120V 500VA BLK-WHT

(Logo)

By: **MX/LL**

(date code)

TOROID CORPORATION of MD