



DATA SHEET FOR
TRANSFORMER # 801.1201

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>	
S#22/8"	0V	WHITE		S#22/8"	
S#22/8"	120V	BLACK		A/R THERMAL SWITCH 120°C UO = 128.8V RMS	S#22/8"
				120V RMS / 100VA	S#22/8"
			GRN/YEL	STATIC SHIELD	S#22/8"


PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120V +/-10%
RATED PRIMARY CURRENT: 0.92A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 37 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 3.9"	WASHER/PADS = 70mm	CORE # 900115
H = 1.8"	THICKNESS = 0.05"	CORE LOSS = 0.7 W
WEIGHT = 2.5 LBS.	HOLE DIAMETER = 0.25"	NO-LOAD CURRENT = 15 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, CUL certified to CSA C22.2 No. 601-1 and meets UL 60601-1 standards. Class B insulation. Leakage current < 100 µA.

Label:	Transformer # 801.1201	
SPEC DATE: 06/04/09	INPUT: 120V 60Hz	SLEEVE (WHT-BLK)
	OUTPUT: 120V/100VA	WHT-BLK
	STATIC SHIELD	GRN/YEL
(Logo)	P/N B01319717	
By: MX	(date code)	

TOROID CORPORATION of MD