



DATA SHEET FOR
TRANSFORMER # 802.1201

Made for STANDARD

LEADS

SCHEMATIC

LEADS

S#20/8"	0V	WHITE		WHITE	0V	S#20/8"	
S#20/8"	120V	BLACK		BLACK	A/R THERMAL SWITCH 120°C UO = 127.2V RMS 120V RMS / 200VA	S#20/8"	
				GRN/YEL	STATIC SHIELD		S#22/8"

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120V +/-10%
RATED PRIMARY CURRENT: 1.81A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 46 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 4.5"	WASHER/PADS = 90mm	CORE # 900225
H = 1.9"	THICKNESS = 0.06"	CORE LOSS = 1.2 W
WEIGHT = 4.1 LBS.	HOLE DIAMETER = 0.25"	NO-LOAD CURRENT = 25 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, CUL certified to CSA C22.2 No. 601-1 and meets UL 60601-1 standards. Class B insulation. Leakage current < 100 µA.

Label:



SPEC DATE: 06/04/09

Transformer # 802.1201

INPUT: 120V 60Hz

SLEEVE (WHT-BLK)

OUTPUT: 120V/200VA

WHT-BLK

STATIC SHIELD

GRN/YEL

(Logo)

P/N B01319718

By: **MX**

(date code)

TOROID CORPORATION of MD