



DATA SHEET FOR
TRANSFORMER # 804.1201

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>	
S#18/8"	0V	WHITE		S#18/8"	
S#18/8"	120V	BLACK		WHITE 0V A/R THERMAL SWITCH 120°C UO = 125.1V RMS BLACK 120V RMS / 400VA GRN/YEL STATIC SHIELD	S#18/8"
					S#20/8"

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120V +/-10%
RATED PRIMARY CURRENT: 3.55A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 52 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 5.5"	WASHER/PADS = 110mm	CORE # 900370
H = 2.1"	THICKNESS = 0.08"	CORE LOSS = 1.7 W
WEIGHT = 6.6 LBS.	HOLE DIAMETER = 0.32"	NO-LOAD CURRENT = 37 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, CUL certified to CSA C22.2 No. 601-1 and meets UL 60601-1 standards. Class B insulation. Leakage current < 100 µA.

Label:	Transformer # 804.1201	
SPEC DATE: 06/04/09	INPUT: 120V 60Hz	SLEEVE (WHT-BLK)
	OUTPUT: 120V/400VA	WHT-BLK
	STATIC SHIELD	GRN/YEL
(Logo)	P/N B01319720	

By: **MX**

(date code)

TOROID CORPORATION of MD