



DATA SHEET FOR
TRANSFORMER # 810.1201

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>	
S#14/8"	0V	WHITE		S#14/8"	
S#14/8"	120V	BLACK		WHITE 0V A/R THERMAL SWITCH 120°C UO = 122.6V RMS	S#14/8"
				BLACK 120V RMS / 1000VA	S#14/8"
				GRN/YEL STATIC SHIELD	S#18/8"


PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120V +/-10%
RATED PRIMARY CURRENT: 8.65A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 50 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 6.4"	WASHER/PADS = 145mm	CORE # 1000
H = 3.1"	THICKNESS = 0.08"	CORE LOSS = 4.4 W
WEIGHT = 14.8 LBS.	HOLE DIAMETER = 0.40"	NO-LOAD CURRENT = 96 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, CUL certified to CSA C22.2 No. 601-1 and meets UL 60601-1 standards. Class B insulation. Leakage current < 100 µA.

Label: 

Transformer # 810.1201

SPEC DATE: 06/04/09 INPUT: 120V 60Hz SLEEVE (WHT-BLK)

OUTPUT: 120V/1000VA WHT-BLK

STATIC SHIELD GRN/YEL

(Logo) P/N B01319723

By: **MX** (date code)

TOROID CORPORATION of MD