



DATA SHEET FOR
TRANSFORMER # 901.1201

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>		
S#22/12"	0V	WHITE		WHITE	0V	S#22/12"
S#22/12"	100V	BLUE			A/R THERMAL FUSE 120° C	
S#22/12"	120V	YELLOW		BLACK	UO = 138.7V RMS	S#22/12"
S#22/12"	0V	ORANGE		VIOLET	120V RMS / 100VA	S#22/12"
S#22/12"	100V	RED			STATIC SHIELD	
S#22/12"	120V	BLACK				


PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
RATED PRIMARY CURRENT: 1.2/1.0/0.5/0.5A
RATED FREQUENCY: 50/60Hz
TEMP. RISE AT RATED LOAD: 60° C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 3.9"	WASHER/PADS = 70 mm.	CORE # 900115
H = 1.8"	THICKNESS = 0.05"	CORE LOSS = 0.7 W
WEIGHT = 2.5 LBS.	HOLE DIAMETER = 0.25"	NO-LOAD CURRENT = 6.4 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized UL 2601-1, CUL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label: 

Transformer # B4316190 (901.1201)
(301001)

SPEC DATE: 03/20/15

By: (Logo) (date code)

TOROID CORPORATION of MD