



DATA SHEET FOR  
TRANSFORMER # 902.1201

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>			
S#22/12"	0V	WHITE		WHITE	0V	S#22/12"	
S#22/12"	100V	BLUE		BLACK	A/R THERMAL FUSE 120° C	UO = 133.4V RMS	S#22/12"
S#22/12"	120V	YELLOW		VIOLET	120V RMS / 200VA		S#22/12"
S#22/12"	0V	ORANGE			STATIC SHIELD		S#22/12"
S#22/12"	100V	RED					
S#22/12"	120V	BLACK					


PRIMARIES ARE INSIDE A SLEEVE.  
Primaries must be connected together in series or in parallel.  
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%  
RATED PRIMARY CURRENT: 2.2/1.9/1.0/0.9A  
RATED FREQUENCY: 50/60Hz  
TEMP. RISE AT RATED LOAD: 63° C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 4.5"	WASHER/PADS = 90 mm.	CORE # 900225
H = 2.1"	THICKNESS = 0.06"	CORE LOSS = 1.2 W
WEIGHT = 4.3 LBS.	HOLE DIAMETER = 0.25"	NO-LOAD CURRENT = 10.5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, CUL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label:   
Transformer # B04316191 (902.1201)  
(302001)  
SPEC DATE: 03/20/15  
By: (Logo) (date code)

TOROID CORPORATION of MD