



DATA SHEET FOR
TRANSFORMER # 906.1201

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>	
S#18/12"	0V	WHITE		S#18/12"	
S#18/12"	100V	BLUE		A/R THERMAL FUSE 120° C	
S#18/12"	120V	YELLOW		UO = 127.9V RMS	S#18/12"
S#18/12"	0V	ORANGE		120V RMS / 600VA	
S#18/12"	100V	RED		VIOLET	S#20/12"
S#18/12"	120V	BLACK		STATIC SHIELD	

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
 RATED PRIMARY CURRENT: 6.4/5.4/2.9/2.7A
 RATED FREQUENCY: 50/60Hz
 TEMP. RISE AT RATED LOAD: 64° C

DIMENSIONS/WEIGHT:
 OD = 6.5"
 H = 2.5"
 WEIGHT = 10.4 LBS.

MOUNTING:
 WASHER/PADS = 145 mm.
 THICKNESS = 0.08"
 HOLE DIAMETER = 0.40"

CORE DATA:
 CORE # 900639
 CORE LOSS = 3.1 W
 NO-LOAD CURRENT = 27.9 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, CUL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label:



SPEC DATE: 03/20/15

Transformer # B04316194
(906.1201) (306001)

(Logo)

By:

(date code)

TOROID CORPORATION of MD