



DATA SHEET FOR
TRANSFORMER # 908.1201

Made for STANDARD

| <u>LEADS</u> | | | <u>SCHEMATIC</u> | <u>LEADS</u> | | |
|--------------|------|--------|------------------|-------------------------|------------------|----------|
| S#18/12" | 0V | WHITE | | WHITE | 0V | S#16/12" |
| S#18/12" | 100V | BLUE | | A/R THERMAL FUSE 120° C | UO = 126.5V RMS | S#16/12" |
| S#18/12" | 120V | YELLOW | | BLACK | 120V RMS / 760VA | S#16/12" |
| S#18/12" | 0V | ORANGE | | VIOLET | STATIC SHIELD | S#20/12" |
| S#18/12" | 100V | RED | | | | |
| S#18/12" | 120V | BLACK | | | | |

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
RATED PRIMARY CURRENT: 8.0/6.7/3.7/3.3A
RATED FREQUENCY: 50/60Hz
TEMP. RISE AT RATED LOAD: 64° C


DIMENSIONS/WEIGHT:
OD = 6.5"
H = 2.8"
WEIGHT = 13.0 LBS.

MOUNTING:
WASHER/PADS = 145 mm.
THICKNESS = 0.08"
HOLE DIAMETER = 0.40"

CORE DATA:
CORE # 800
CORE LOSS = 3.5 W
NO-LOAD CURRENT = 31.9 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, CUL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label: 
 Transformer # B04316195 (908.1201)
 (307601)

SPEC DATE: 03/20/15
 By: (Logo) (date code)

TOROID CORPORATION of MD