



DATA SHEET FOR  
TRANSFORMER # 908.1202

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>
S#16/12"	0V	WHITE	BROWN	S#18/12"
S#16/12"	100V	BLUE	RED	S#18/12"
S#16/12"	120V	YELLOW	ORANGE	S#18/12"
S#16/12"	0V	ORANGE	YELLOW	S#18/12"
S#16/12"	100V	RED	VIOLET	S#18/12"
S#16/12"	120V	BLACK		S#18/12"

A/R THERMAL FUSE 120°C  
UO = 126.4V RMS  
120V RMS / 380VA

A/R THERMAL FUSE 120°C  
UO = 126.4V RMS  
120V RMS / 380VA

STATIC SHIELD


PRIMARIES ARE INSIDE A SLEEVE.  
Primaries must be connected together in series or in parallel.  
LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%  
RATED PRIMARY CURRENT: 8.1/6.7/4.1/3.7/3.4A  
RATED FREQUENCY: 50/60 Hz  
TEMP. RISE AT RATED LOAD: 63°C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 6.5"	WASHER/PADS = 145 M.M./5.7"	CORE # 800
H = 2.8"	THICKNESS = .08"	NO-LOAD LOSS = 3.5 W
WEIGHT = 12.5 LBS.	HOLE DIAMETER = .40"	NO-LOAD AMPS = 31 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, CUL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label: 

Transformer # B04315233 (908.1202)  
(307602)

SPEC DATE: 03/20/15

By: (Logo) (date code)

TOROID CORPORATION of MD