



DATA SHEET FOR
TRANSFORMER # 915.1201

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>			
S#14/12"	0V	WHITE		WHITE	0V	S#12/12"	
S#14/12"	100V	BLUE		A/R THERMAL FUSE 120° C	UO = 124.5V RMS		
S#14/12"	120V	YELLOW		BLACK	120V RMS / 1500VA		S#12/12"
S#14/12"	0V	ORANGE		VIOLET	STATIC SHIELD		S#18/12"
S#14/12"	100V	RED					
S#14/12"	120V	BLACK					

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
RATED PRIMARY CURRENT: 15.7/13.0/7.1/6.5A
RATED FREQUENCY: 50/60Hz
TEMP. RISE AT RATED LOAD: 60° C



DIMENSIONS/WEIGHT:
OD = 8.2"
H = 3.6"
WEIGHT = 23.6 LBS.

MOUNTING:
SPECIFIED BY CUSTOMER

CORE DATA:
CORE # 1700
CORE LOSS = 6.7 W
NO-LOAD CURRENT = 59.1 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, CUL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label:  

Transformer # B04316197 (915.1201)
(315001)

SPEC DATE: 03/20/15 (Logo) (date code)

By: (date code)

TOROID CORPORATION of MD