



DATA SHEET FOR
TRANSFORMER # 920.1201

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>	
S#12/12"	0V	WHITE		S#10/12"	
S#12/12"	100V	BLUE		A/R THERMAL FUSE 120° C	S#10/12"
S#12/12"	120V	YELLOW		UO = 124.1V RMS	S#10/12"
S#12/12"	0V	ORANGE		120V RMS / 2000VA	S#18/12"
S#12/12"	100V	RED		STATIC SHIELD	
S#12/12"	120V	BLACK			

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
RATED PRIMARY CURRENT: 20.8/17.3/9.5/8.7A
RATED FREQUENCY: 50/60Hz
TEMP. RISE AT RATED LOAD: 58° C


DIMENSIONS/WEIGHT:
OD = 9.2"
H = 4.1"
WEIGHT = 31.0 LBS.

MOUNTING:
SPECIFIED BY CUSTOMER

CORE DATA:
CORE # 902047
CORE LOSS = 8.4 W
NO-LOAD CURRENT = 71.7 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1. CUL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label: 

Transformer # B04316198 (920.1201)
(320001)

SPEC DATE: 03/20/15 (Logo) (date code)

By: (date code)

TOROID CORPORATION of MD