



DATA SHEET FOR
TRANSFORMER # 920.1202

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>	
S#12/12"	0V	WHITE		S#12/12"	
S#12/12"	100V	BLUE		BROWN 0V A/R THERMAL FUSE 120°C UO = 124.0V RMS	S#12/12"
S#12/12"	120V	YELLOW		RED 120V RMS / 1000VA	S#12/12"
S#12/12"	0V	ORANGE		ORANGE 0V A/R THERMAL FUSE 120°C UO = 124.0V RMS	S#12/12"
S#12/12"	100V	RED		YELLOW 120V RMS / 1000VA	S#12/12"
S#12/12"	120V	BLACK		VIOLET STATIC SHIELD	S#18/12"

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
RATED PRIMARY CURRENT: 21/18/11/10/9A
RATED FREQUENCY: 50/60 Hz
TEMP. RISE AT RATED LOAD: 55°C

DIMENSIONS/WEIGHT:
OD = 10.0"
H = 4.0"
WEIGHT = 32.5 LBS.

MOUNTING:
SPECIFIED BY CUSTOMER

CORE DATA:
CORE # 902002
NO-LOAD LOSS = 8.4 W
NO-LOAD AMPS = 72 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, CUL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label:



Transformer # B04313354 (920.1202)
(320002)

SPEC DATE: 03/20/15

(Logo)

By:

(date code)

TOROID CORPORATION of MD