



DATA SHEET FOR
TRANSFORMER # 925.1202

Made for STANDARD

| <u>LEADS</u> | | <u>SCHEMATIC</u> | | <u>LEADS</u> | | | |
|--------------|------|------------------|--|------------------------|--------|-------------------|----------|
| S#12/12" | 0V | WHITE | | BROWN | 0V | S#12/12" | |
| S#12/12" | 100V | BLUE | | A/R THERMAL FUSE 120°C | | | |
| S#12/12" | 120V | YELLOW | | UO = 123.3V RMS | RED | 120V RMS / 1250VA | S#12/12" |
| S#12/12" | 0V | ORANGE | | 0V | ORANGE | 0V | S#12/12" |
| S#12/12" | 100V | RED | | A/R THERMAL FUSE 120°C | YELLOW | 120V RMS / 1250VA | S#12/12" |
| S#12/12" | 120V | BLACK | | 120V RMS / 1250VA | VIOLET | STATIC SHIELD | S#18/12" |

PRIMARIES ARE INSIDE A SLEEVE.
Primaries must be connected together in series or in parallel.
LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%
RATED PRIMARY CURRENT: 26/22/13/12/11A
RATED FREQUENCY: 50/60 Hz
TEMP. RISE AT RATED LOAD: 60°C

DIMENSIONS/WEIGHT:
OD = 11.0"
H = 4.0"
WEIGHT = 38.5 LBS.

MOUNTING:
SPECIFIED BY CUSTOMER

CORE DATA:
CORE # 902326
NO-LOAD LOSS = 10.2 W
NO-LOAD AMPS = 87 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, CUL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label:



Transformer # B04313355 (925.1202)
(325002)

SPEC DATE: 03/20/15

(Logo)

By:

(date code)

TOROID CORPORATION of MD