



DATA SHEET FOR  
TRANSFORMER # 930.1202

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>			
S#12/12"	0V	WHITE		BROWN	0V	S#12/12"	
S#12/12"	100V	BLUE		A/R THERMAL FUSE 120°C			
S#12/12"	120V	YELLOW		RED	120V RMS / 1500VA		S#12/12"
S#12/12"	0V	ORANGE		ORANGE	0V		S#12/12"
S#12/12"	100V	RED		A/R THERMAL FUSE 120°C	120V RMS / 1500VA		S#12/12"
S#12/12"	120V	BLACK		YELLOW	120V RMS / 1500VA		S#12/12"
			VIOLET	STATIC SHIELD		S#18/12"	

PRIMARIES ARE INSIDE A SLEEVE.  
Primaries must be connected together in series or in parallel.  
LEADS: S=Multistranded Lead wire. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 100/120/220/240V +/-10%  
RATED PRIMARY CURRENT: 31/26/16/15/13A  
RATED FREQUENCY: 50/60 Hz  
TEMP. RISE AT RATED LOAD: 54°C


DIMENSIONS/WEIGHT:  
OD = 11.0"  
H = 4.5"  
WEIGHT = 50.0 LBS.

MOUNTING:  
SPECIFIED BY CUSTOMER

CORE DATA:  
CORE # 902906  
NO-LOAD LOSS = 13.3 W  
NO-LOAD AMPS = 112 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 2601-1, CUL certified to CSA C22.2 No. 601-1 and TUV certified to EN60601 and EN60742. CE compliance. Class B insulation. Leakage current < 50µA.

Label: 

Transformer # B04313356 (930.1202)  
(330002)

SPEC DATE: 03/20/15

By: (Logo) (date code)

TOROID CORPORATION of MD