



DATA SHEET FOR
TRANSFORMER # 604.122

Made for STANDARD

LEADS

SCHEMATIC

LEADS

S#22/8"	0V	WHITE		BROWN	0V	UO = 14.6V RMS	M#21/8"
S#22/8"	117V	WHITE		RED	12V RMS / 1.75A RMS		M#21/8"
				ORANGE	0V	UO = 14.6V RMS	M#21/8"
				YELLOW	12V RMS / 1.75A RMS		M#21/8"

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded wire. M=Magnet wire self leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 0.4A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 60 °C

DIMENSIONS/WEIGHT:
OD = 2.8"
H = 1.3"
WEIGHT = 1.1 LBS.

MOUNTING:
WASHER/PADS = 50mm
THICKNESS = 0.04"
HOLE DIAMETER = 0.17"

CORE DATA:
CORE # 30
CORE LOSS = 0.2 W
NO-LOAD CURRENT = 5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506, UL1411 and CUL certified to CSA C22.2 No. 66 standards. ROHS compliance.

Label:



Transformer # 604.122 (U2009)
PRIM. 117V 60HZ BK+(WH-WH)
SEC. 2x12V/1.75A BN-RE/OR-YE

SPEC DATE: 09/20/18

(Logo)

By: *MX/LL*

(date code)

TOROID CORPORATION