

DATA SHEET FOR  
TRANSFORMER # 604.182

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>	
S#22/8"      0V      WHITE		M#23/8"	
S#22/8"      117V      WHITE		UO = 22.1V RMS 18V RMS / 1.17A RMS	M#23/8"
		ORANGE      0V	M#23/8"
		YELLOW      18V RMS / 1.17A RMS	M#23/8"

PRIMARIES ARE INSIDE A SLEEVE.

LEADS: S=Multistranded Lead wire. M=Magnet wire self-leads. Length tolerance: +/-1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY:            117V +/-10%  
RATED PRIMARY CURRENT: 0.4A

RATED FREQ.: 60 Hz  
TEMP RISE AT RATED LOAD = 63 C

DIMENSIONS/WEIGHT:  
OD = 2.8"  
H = 1.3"  
WEIGHT = 1.1 LBS.

MOUNTING:  
WASHER/PADS = 50 mm  
THICKNESS = 0.04"  
HOLE DIAMETER = 0.17"

CORE DATA:  
CORE # 30  
NO-LOAD LOSS = 0.2 W  
NO-LOAD AMPS = 5 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66.

	Label:	
SPEC DATE:    2/22/96	(LOGO)	Transformer # 604.182 (100422) Prim. 117V 60 Hz bk+(wh-wh) Sec. 2x18V/1.17A br-re/or-ye (date code)
BY:		