



DATA SHEET FOR  
TRANSFORMER # 604.242

Made for STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>	
S#22/8"	0V	WHITE		BROWN	0V	M#24/8"	
S#22/8"	117V	WHITE		RED	24V RMS / 0.88A RMS	M#24/8"	
				ORANGE	0V	M#24/8"	
				YELLOW	24V RMS / 0.88A RMS	M#24/8"	

PRIMARIES ARE INSIDE A SLEEVE.

LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%  
RATED PRIMARY CURRENT: 0.4A  
RATED FREQUENCY: 60 Hz  
TEMP. RISE AT RATED LOAD: 61 °C

DIMENSIONS/WEIGHT:  
OD = 2.8"  
H = 1.3"  
WEIGHT = 1.1 LBS.

MOUNTING:  
WASHER/PADS = 50mm  
THICKNESS = 0.04"  
HOLE DIAMETER = 0.17"

CORE DATA:  
CORE # 30  
CORE LOSS = 0.2 W  
NO-LOAD CURRENT = 5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506 and CSA C22.2 No. 66 standards.

Label: Transformer # 604.242  
PRIM. 117V 60Hz BK(WH-WH)  
SEC. 2x24V/0.88A BR-RD/OR-YE  
(date code)

SPEC DATE: 08/08/05

By: (Logo)

TOROID CORPORATION of MD