



DATA SHEET FOR
TRANSFORMER # 607.082

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>		
S#25/8"	0V	WHITE		BROWN	0V	M#18/8"
S#25/8"	117V	WHITE		RED	8.5V RMS / 3.94A RMS	M#18/8"
				ORANGE	0V	M#18/8"
				YELLOW	8.5V RMS / 3.94A RMS	M#18/8"

PRIMARIES ARE INSIDE A SLEEVE.

LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 0.7A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 60 °C


DIMENSIONS/WEIGHT:
OD = 3.2"
H = 1.4"
WEIGHT = 1.5 LBS.

MOUNTING:
WASHER/PADS = 60mm
THICKNESS = 0.05"
HOLE DIAMETER = 0.20"

CORE DATA:
CORE # 50
CORE LOSS = 0.4 W
NO-LOAD CURRENT = 9 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506 and CSA C22.2 No. 66 standards.

Label: Transformer # 607.082 (100702) 

By: (Logo) PRIM. 117V 60Hz BK(WH-WH)

SEC. 2x8.5V/3.94A BR-RD/OR-YE

(date code)

SPEC DATE: 08/08/05

TOROID CORPORATION of MD