

DATA SHEET FOR

TRANSFORMER # 607.122

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>													
M#25/8" 0V WHITE		M#20/8"													
M#25/8" 117V WHITE		<table border="0" style="width: 100%;"> <tr> <td style="width: 30%;">BROWN</td> <td style="width: 30%;">0V</td> <td style="width: 30%;">UO = 13.9V RMS</td> </tr> <tr> <td>RED</td> <td>12V RMS / 2.58A RMS</td> <td></td> </tr> <tr> <td>ORANGE</td> <td>0V</td> <td>UO = 13.9V RMS</td> </tr> <tr> <td>YELLOW</td> <td>12V RMS / 2.58A RMS</td> <td></td> </tr> </table>	BROWN	0V	UO = 13.9V RMS	RED	12V RMS / 2.58A RMS		ORANGE	0V	UO = 13.9V RMS	YELLOW	12V RMS / 2.58A RMS		M#20/8"
BROWN		0V	UO = 13.9V RMS												
RED		12V RMS / 2.58A RMS													
ORANGE	0V	UO = 13.9V RMS													
YELLOW	12V RMS / 2.58A RMS														
		M#20/8"													
		M#20/8"													

PRIMARIES ARE INSIDE A SLEEVE.

LEADS: S=Multistranded Lead wire. M=Magnet wire self-leads. Length tolerance: +/-1/2".
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
 RATED PRIMARY CURRENT: 0.7A

RATED FREQ.: 60 Hz
 TEMP RISE AT RATED LOAD = 56 C

DIMENSIONS/WEIGHT:
 OD = 3.2"
 H = 1.4"
 WEIGHT = 1.4 LBS.

MOUNTING:
 WASHER/PADS = 60 mm
 THICKNESS = 0.05"
 HOLE DIAMETER = 0.25"

CORE DATA:
 CORE # 50
 NO-LOAD LOSS = 0.4 W
 NO-LOAD AMPS = 8 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66.

SPEC DATE: 3/05/96 BY:	Label: (LOGO)	Transformer # 607.122 (100622) Prim. 117V 60 Hz bk+(wh-wh) Sec. 2x12V/2.58A br-re/or-ye (date code)
----------------------------------	----------------------	--