

# DATA SHEET FOR

## TRANSFORMER # 607.182

STANDARD

page 1 of 1

<u>LEADS</u>		<u>SCHEMATIC</u>			<u>LEADS</u>	
M#25/8"	0V	WHITE		BROWN	0V	M#22/8"
M#25/8"	117V	BLACK		RED	$U_0 = 21.1V \text{ RMS}$ 18V RMS / 1.72A RMS	M#22/8"
				ORANGE	0V	M#22/8"
				YELLOW	$U_0 = 21.1V \text{ RMS}$ 18V RMS / 1.72A RMS	M#22/8"

PRIMARIES ARE INSIDE A SLEEVE.  
 LEADS: M=Magnet wire self-leads. Length tolerance: +/- 1/2".  
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/- 10%	RATED FREQ.: 60 Hz
RATED PRIMARY CURRENT: 0.62A	TEMP RISE AT RATED LOAD = 60 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 3.2 "	WASHER/PADS = 60mm	CORE # 50
H = 1.4 "	THICKNESS = 0.05 "	NO-LOAD LOSS = 0.4 W
WEIGHT = 1.4 LBS.	HOLE DIAMETER = 0.20 "	NO-LOAD AMPS < 9.2 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No.66.

SPEC DATE: 7/23/97	Label:	
	(LOGO)	Transformer # 607.182
		Prim. 117v 60Hz bk+(wh-wh)
		Sec. 2x18V/1.72A br-re/or-yel
BY: _____		(date code)