

DATA SHEET FOR

TRANSFORMER # 607.242


STANDARD

page 1 of 1

LEADS

M#25/8" 0V WHITE
M#25/8" 117V BLACK

SCHEMATIC



BROWN 0V
 U₀ = 27.9V RMS
 24V RMS / 1.29A RMS
ORANGE 0V
 U₀ = 27.9V RMS
 24V RMS / 1.29A RMS
YELLOW

LEADS

M#23/8"
M#23/8"
M#23/8"
M#23/8"

PRIMARIES ARE INSIDE A SLEEVE.

LEADS: M=Magnet wire self-leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/- 10%
RATED PRIMARY CURRENT: 0.62A

RATED FREQ.: 60 Hz
TEMP RISE AT RATED LOAD = 57°C

DIMENSIONS/WEIGHT:

OD = 3.2 "
H = 1.4 "
WEIGHT = 1.4 LBS.

MOUNTING:

WASHER/PADS = 60mm
THICKNESS = 0.05 "
HOLE DIAMETER = 0.20 "

CORE DATA:

CORE # 50
NO-LOAD LOSS = 0.4 W
NO-LOAD AMPS < 9.2 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No.66.

SPEC DATE: 7/23/97

BY: _____

Label:
(LOGO)

Transformer # 607.242
Prim. 117v 60Hz bk+(wh-wh)
Sec. 2x24V/1.29A br-re/or-yel
(date code)