

DATA SHEET FOR

TRANSFORMER # 612.082

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>
M#22/8" 0V WHITE		M#15/8"
M#22/8" 117V WHITE		M#15/8"
		M#15/8"
		M#15/8"

PRIMARIES ARE INSIDE A SLEEVE.

LEADS: M=Magnet wire self-leads. Length tolerance: +/-1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 1.1A

RATED FREQ.: 60 Hz
TEMP RISE AT RATED LOAD = 53 C

DIMENSIONS/WEIGHT:
OD = 3.9"
H = 1.5"
WEIGHT = 2.2 LBS.

MOUNTING:
WASHER / PADS = 90 mm
THICKNESS = 0.05"
HOLE DIAMETER = 0.25"

CORE DATA:
CORE # 900095
NO-LOAD LOSS = 0.7 W
NO-LOAD AMPS = 12 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66.

	Label:	
SPEC DATE: 3/05/96	(LOGO)	Transformer # 612.082 (101102) Prim. 117V 60 Hz bk+(wh-wh) Sec. 2x8.5V/6.47A br-re/or-ye (date code)
BY:		