

DATA SHEET FOR

TRANSFORMER # 612.122

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>	<u>LEADS</u>
M#22/8" 0V WHITE		M#17/8"
M#22/8" 117V WHITE		M#17/8"
		M#17/8"
		M#17/8"

PRIMARIES ARE INSIDE A SLEEVE.

LEADS: M=Magnet wire self-leads. Length tolerance: +/-1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
 RATED PRIMARY CURRENT: 1.2A

RATED FREQ.: 60 Hz
 TEMP RISE AT RATED LOAD = 59 C

DIMENSIONS/WEIGHT:
 OD = 3.9"
 H = 1.5"
 WEIGHT = 2.2 LBS.

MOUNTING:
 WASHER/PADS = 70 mm
 THICKNESS = 0.05"
 HOLE DIAMETER = 0.25"

CORE DATA:
 CORE # 900095
 NO-LOAD LOSS = 0.6 W
 NO-LOAD AMPS = 12 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66.

SPEC DATE: 8/5/96 BY: _____	Label: (LOGO)	Transformer # 612.122 (101102) Prim. 117V 60 Hz bk+(wh-wh) Sec. 2x12V/4.58A br-re/or-ye (date code)
---------------------------------------	----------------------	--