



DATA SHEET FOR
TRANSFORMER # 617.122

Made for STANDARD

page 1 of 1

| <u>LEADS</u> | | <u>SCHEMATIC</u> | | <u>LEADS</u> | | |
|--------------|------|------------------|--|--------------|---------------------|---------|
| M#20/8" | 0V | WHITE | | BROWN | 0V | M#15/8" |
| M#20/8" | 117V | WHITE | | RED | 12V RMS / 7.25A RMS | M#15/8" |
| | | | | ORANGE | 0V | M#15/8" |
| | | | | YELLOW | 12V RMS / 7.25A RMS | M#15/8" |

PRIMARIES ARE INSIDE A SLEEVE.

LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 1.6A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 66 °C

DIMENSIONS/WEIGHT:
OD = 3.9"
H = 1.9"
WEIGHT = 3.2 LBS.

MOUNTING:
WASHER/PADS = 70mm
THICKNESS = 0.05"
HOLE DIAMETER = 0.25"

CORE DATA:
CORE # 900140
CORE LOSS = 0.9 W
NO-LOAD CURRENT = 19 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506 and CSA C22.2 No. 66 standards.

Label: Transformer # 617.122
PRIM. 117V 60Hz BK(WH-WH)
SEC. 2x12V/7.25A BR-RD/OR-YE
(date code)

SPEC DATE: 08/08/05

By: (Logo)

TOROID CORPORATION of MD