



DATA SHEET FOR
TRANSFORMER # 660.220

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>		
M#15/8"	0V	WHITE		BROWN	0V	M#18/8"
M#15/8"	117V	WHITE		BROWN	220V RMS / 2.60A RMS	M#18/8"

UO = 231.5V RMS


PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 5.1A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 61 °C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 5.5"	WASHER/PADS = 110mm	CORE # 500
H = 2.4"	THICKNESS = 0.08"	CORE LOSS = 2.3 W
WEIGHT = 8.1 LBS.	HOLE DIAMETER = 0.32"	NO-LOAD CURRENT = 52 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506 and CSA C22.2 No. 66 standards.

Label:  Transformer # 660.220 (106002)
 SPEC DATE: 08/09/05 PRIM. 117V 60Hz BK(WH-WH)
 (Logo) SEC. 220V/2.60A BRN-BRN
 By: (date code)

TOROID CORPORATION of MD