



DATA SHEET FOR
TRANSFORMER # 660.302

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>		<u>LEADS</u>		
M#15/8"	0V	WHITE		BROWN	0V	M#12/8"
M#15/8"	117V	WHITE		RED	30V RMS / 10.0A RMS	M#12/8"
				ORANGE	0V	M#12/8"
				YELLOW	30V RMS / 10.0A RMS	M#12/8"

PRIMARIES ARE INSIDE A SLEEVE.

LEADS: S=Multistranded wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117V +/-10%
RATED PRIMARY CURRENT: 5.2A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 60 °C


DIMENSIONS/WEIGHT:
OD = 5.5"
H = 2.4"
WEIGHT = 8.1 LBS.

MOUNTING:
WASHER/PADS = 110mm
THICKNESS = 0.08"
HOLE DIAMETER = 0.32"

CORE DATA:
CORE # 500
CORE LOSS = 2.3 W
NO-LOAD CURRENT = 52 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 506 and CSA C22.2 No. 66 standards.

Label:  Transformer # 660.302 (106002)
SPEC DATE: 08/08/05 (Logo) PRIM. 117V 60Hz BK(WH-WH)
By: SEC. 2x30V/10.0A BR-RD/OR-YE
(date code)

TOROID CORPORATION of MD