

DATA SHEET FOR TRANSFORMER # 701.122

STANDARD

page 1 of 1

LEADS	SCHEMATIC			LEADS
S#22/8" 0V WHITE	┌───┐		┌───┐	BROWN 0V
S#22/8" 117V YELLOW	┌───┐		┌───┐	RED $U_0 = 16.4V$ RMS 12V RMS / 0.79A RMS
S#22/8" 0V ORANGE	┌───┐		┌───┐	ORANGE 0V
S#22/8" 117V BLACK	┌───┐		┌───┐	YELLOW $U_0 = 16.4V$ RMS 12V RMS / 0.79A RMS

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded wires. M=Magnet wire self-leads. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/-10%

RATED PRIMARY CURRENT: 0.2/0.1A

RATED FREQ.: 50/60 Hz

TEMP RISE AT RATED LOAD = 64°C

DIMENSIONS/WEIGHT:

OD = 2.4"

H = 1.2"

WEIGHT = 0.7 LBS.

MOUNTING:

WASHER/PADS = 50mm

THICKNESS = 0.04"

HOLE DIAMETER = 0.17"

CORE DATA:

CORE # 15

NO-LOAD LOSS = 0.2 W

NO-LOAD AMPS < 2 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66-1988.

SPEC DATE: 8/25/94	┌───┐	Label:	Transformer # 701.122 (200192)
	(LOGO)		Prim. 2x117V 50/60Hz bk(wh-ye/or-bk)
BY: _____	┌───┐		Sec. 2x12V / 0.79A br-re/or-ye (date code)