

DATA SHEET FOR

TRANSFORMER # 704.122

STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>			<u>LEADS</u>
S#22/8" 0V WHITE	┌───┐		┌───┐	BROWN 0V M#23/8"
S#22/8" 117V YELLOW	┌───┐		┌───┐	RED $U_0 = 15.6V \text{ RMS}$ 12V RMS / 1.38A RMS M#23/8"
S#22/8" 0V ORANGE	┌───┐		┌───┐	ORANGE 0V M#23/8"
S#22/8" 117V BLACK	┌───┐		┌───┐	YELLOW $U_0 = 15.6V \text{ RMS}$ 12V RMS / 1.38A RMS M#23/8"

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded wires. M=Magnet wire self-leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/-10%
RATED PRIMARY CURRENT: 0.4/0.2A

RATED FREQ.: 50/60 Hz
TEMP RISE AT RATED LOAD = 65 °C

DIMENSIONS/WEIGHT:
OD = 2.8"
H = 1.3"
WEIGHT = 1.1 LBS.

MOUNTING:
WASHER/PADS = 50mm
THICKNESS = 0.04"
HOLE DIAMETER = 0.17"

CORE DATA:
CORE # 30
NO-LOAD LOSS = 0.2 W
NO-LOAD AMPS < 2.5 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66-1988.

SPEC DATE: 8/25/94	┌───┐	Label:	┌───┐
	(LOGO)		Transformer # 704.122 (200332)
			Prim. 2x117V 50/60Hz bk(wh-ye/or-bk)
			Sec. 2x12V / 1.38A br-re/or-ye
BY: _____	┌───┐		(date code) ┌───┐