

# DATA SHEET FOR

## TRANSFORMER # 707.062

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>				<u>LEADS</u>
S#22/8"    0V    WHITE	┌───┐		┌───┐	BROWN    0V	M#17/8"
S#22/8"    117V    YELLOW	┌───┐		┌───┐	RED    6.0V RMS / 4.50A RMS	M#17/8"
S#22/8"    0V    ORANGE	┌───┐		┌───┐	ORANGE    0V	M#17/8"
S#22/8"    117V    BLACK	┌───┐		┌───┐	YELLOW    6.0V RMS / 4.50A RMS	M#17/8"

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded Lead wire. M=Magnet wire self-leads. Length tolerance: +/-1/2".  
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY:            117/234V +/-10%  
 RATED PRIMARY CURRENT: 0.6/0.3A

RATED FREQ.: 50/60 Hz  
 TEMP RISE AT RATED LOAD = 61 C

DIMENSIONS/WEIGHT:  
 OD = 3.2"  
 H = 1.4"  
 WEIGHT = 1.5 LBS.

MOUNTING:  
 WASHER/PADS = 60 mm  
 THICKNESS = 0.05"  
 HOLE DIAMETER = 0.20"

CORE DATA:  
 CORE # 50  
 NO-LOAD LOSS = 0.4 W  
 NO-LOAD AMPS = 4.1 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66.

SPEC DATE:    10/16/96	┌───┐	Label:	┌───┐
			Transformer # 707.062 (200542)
			Prim. 2x117V 50/60Hz bk(wh-ye/or-bk)
			Sec. 2x6V / 4.50A br-re/or-ye
BY: _____	┌───┐	(LOGO)	┌───┐
			(date code)