

# DATA SHEET FOR

## TRANSFORMER # 707.092

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>				<u>LEADS</u>
S#22/8"    0V    WHITE	┌───┐		┌───┐	BROWN    0V	M#19/8"
S#22/8"    117V    YELLOW	┌───┐		┌───┐	RED    UO = 10.9V RMS 9V RMS / 3.00A RMS	M#19/8"
S#22/8"    0V    ORANGE	┌───┐		┌───┐	ORANGE    0V	M#19/8"
S#22/8"    117V    BLACK	┌───┐		┌───┐	YELLOW    UO = 10.9V RMS 9V RMS / 3.00A RMS	M#19/8"

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded Lead wire. M=Magnet wire self-leads. Length tolerance: +/-1/2".  
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY:            117/234V +/-10%  
RATED PRIMARY CURRENT: 0.6/0.3A

RATED FREQ.: 50/60 Hz  
TEMP RISE AT RATED LOAD = 63 C

DIMENSIONS/WEIGHT:  
OD = 3.2"  
H = 1.4"  
WEIGHT = 1.5 LBS.

MOUNTING:  
WASHER/PADS = 60 mm  
THICKNESS = 0.05"  
HOLE DIAMETER = 0.20"

CORE DATA:  
CORE # 50  
NO-LOAD LOSS = 0.4 W  
NO-LOAD AMPS = 4.1 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66.

SPEC DATE:    10/16/96	┌───┐	Label:	┌───┐	
				Transformer # 707.092 (200542)
				Prim. 2x117V 50/60Hz bk(wh-ye/or-bk)
				Sec. 2x 9V / 3.00A br-re/or-ye
BY: _____	┌───┐	(LOGO)	┌───┐	
				(date code)