

# DATA SHEET FOR

## TRANSFORMER # 713.152

Made for STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>			<u>LEADS</u>	
M#24/8"    0V    WHITE	┌───┐		┌───┐	BROWN    0V	M#17/8"
M#24/8"    117V    YELLOW	┌───┐		┌───┐	RED    15V RMS / 4.67A RMS	M#17/8"
M#24/8"    0V    ORANGE	┌───┐		┌───┐	ORANGE    0V	M#17/8"
M#24/8"    117V    BLACK	┌───┐		┌───┐	YELLOW    15V RMS / 4.67A RMS	M#17/8"

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: S=Multistranded Lead wire. M=Magnet wire self-leads. Length tolerance: +/-1/2".  
 Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY:            117/234V +/-10%  
 RATED PRIMARY CURRENT: 1.4/0.7A

RATED FREQ.: 50/60 Hz  
 TEMP RISE AT RATED LOAD = 65 C

DIMENSIONS/WEIGHT:

OD = 3.9"  
 H = 1.9"  
 WEIGHT = 3.0 LBS.

MOUNTING:

WASHER/PADS = 70 mm  
 THICKNESS = 0.05"  
 HOLE DIAMETER = 0.25"

CORE DATA:

CORE # 900140  
 NO-LOAD LOSS = 0.9 W  
 NO-LOAD AMPS = 8.7 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66.

SPEC DATE: 10/16/96	┌───┐	Label:	┌───┐	
		Transformer # 713.152 (201402)		
		Prim. 2x117V 50/60Hz bk(wh-ye/or-bk)		
		Sec. 2x15V / 4.67A br-re/or-ye		
BY: _____	┌───┐	(LOGO)	┌───┐	(date code)