







DATA SHEET FOR TRANSFORMER # 718.152

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>	
M#22/8"	0V	white			brown	0V	M#16/8"
M#22/8"	117V	yellow			red	15V rms at 6.00A rms	M#16/8"
M#22/8"	0V	orange			orange	0V	M#16/8"
M#22/8"	117V	black			yellow	15V rms at 6.00A rms	M#16/8"

PRIMARY LEADS ARE INSIDE A BLACK SLEEVE. Primaries must be connected in series or in parallel.
LEADS: S=Multistranded lead wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".
Manufacturing tolerance is 3%.

NOMINAL SUPPLY: 117/234 V +/- 10% **RATED FREQ.:** 50/60 Hz
RATED PRIMARY CURRENT: 1.8/.9 A **TEMP RISE AT RATED LOAD =** 63 C

<u>DIMENSIONS/WEIGHT:</u> OD = 4.5" H = 1.8" WEIGHT = 3.8 lbs.	<u>MOUNTING:</u> WASHER/PADS = 90 mm THICKNESS = .06" HOLE DIAMETER = .25"	<u>CORE DATA:</u> CORE # 900175 NO-LOAD LOSS = 1 W NO-LOAD AMPS = 9.5 mA
--	--	--

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66-1988.

SPEC. DATE: 08-25-94 BY: _____	Label: (LOGO)	Transformer # 718.152 (201802) Prim. 2x117V 50Hz bk(wh-ye/or-bk) Sec. 2x15V / 6.00A br-re/or-ye (date code)
---------------------------------------	----------------------	--