

DATA SHEET FOR TRANSFORMER # 718.242

Made for STANDARD

<u>LEADS</u>	<u>SCHEMATIC</u>				<u>LEADS</u>
M#22/8" 0V white	□		□	brown 0V	M#18/8"
M#22/8" 117V yellow	□		□	red 24V rms at 3.75A rms	M#18/8"
M#22/8" 0V orange	□		□	orange 0V	M#18/8"
M#22/8" 117V black	□		□	yellow 24V rms at 3.75A rms	M#18/8"

PRIMARY LEADS ARE INSIDE A BLACK SLEEVE. Primaries must be connected in series or in parallel.
 LEADS: S=Multistranded lead wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".
 Manufacturing tolerance is 3%.

NOMINAL SUPPLY:	117/234 V +/- 10%	RATED FREQ.: 50/60 Hz
RATED PRIMARY CURRENT:	1.8/.9 A	TEMP RISE AT RATED LOAD = 63 C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 4.5"	WASHER/PADS = 90 mm	CORE # 900175
H = 1.8"	THICKNESS = .06"	NO-LOAD LOSS = 1 W
WEIGHT =3.8 lbs.	HOLE DIAMETER = .25"	NO-LOAD AMPS =9.5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66-1988.

SPEC. DATE: 08-25-94 BY: _____	Label: (LOGO) Transformer # 718.242 (201802) Prim. 2x117V 50Hz bk(wh-ye/or-bk) Sec. 2x24V / 3.75A br-re/or-ye (date code)
---------------------------------------	--