

DATA SHEET FOR TRANSFORMER # 718.302

Made for STANDARD

<u>LEADS</u>		<u>SCHEMATIC</u>				<u>LEADS</u>	
M#22/8"	0V	white	□	□	brown	0V	M#19/8"
M#22/8"	117V	yellow	□	□	red	(U0= 33.7V rms) 30V rms at 3.00A rms	M#19/8"
M#22/8"	0V	orange	□	□	orange	0V	M#19/8"
M#22/8"	117V	black	□	□	yellow	(U0= 33.7V rms) 30V rms at 3.00A rms	M#19/8"

PRIMARY LEADS ARE INSIDE A BLACK SLEEVE. Primaries must be connected in series or in parallel.

LEADS: S=Multistranded lead wire. M=Magnet wire self-leads. Length tolerance: +/- 1/2".

Manufacturing tolerance is 3%.

NOMINAL SUPPLY: 117/234 V +/- 10% RATED FREQ.: 50/60 Hz
RATED PRIMARY CURRENT: 1.8/.9 A TEMP RISE AT RATED LOAD = 64 C

<u>DIMENSIONS/WEIGHT:</u>	<u>MOUNTING:</u>	<u>CORE DATA:</u>
OD = 4.5"	WASHER/PADS = 90 mm	CORE # 900175
H = 1.8"	THICKNESS = .06"	NO-LOAD LOSS = 1 W
WEIGHT =3.8 lbs.	HOLE DIAMETER = .25"	NO-LOAD AMPS =9.5 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66-1988.

┌ Label:

SPEC.DATE: 08-25-94

(LOGO)

Transformer # 718.302 (201802)
Prim. 2x117V 50Hz bk(wh-ye/or-bk)
Sec. 2x30V / 3.00A br-re/or-ye
(date code)

BY: _____