

DATA SHEET FOR

TRANSFORMER # 749.242

STANDARD

page 1 of 1

<u>LEADS</u>			<u>SCHEMATIC</u>			<u>LEADS</u>
M#18/8"	0V	WHITE	┌───┐		┌───┐	M#13/8"
M#18/8"	117V	YELLOW	└───┘		└───┘	M#13/8"
M#18/8"	0V	ORANGE	┌───┐		┌───┐	M#13/8"
M#18/8"	117V	BLACK	└───┘		└───┘	M#13/8"
					BROWN	0V
					RED	U ₀ = 25.7V RMS
					ORANGE	24V RMS / 9.79A RMS
					YELLOW	0V
						U ₀ = 25.7V RMS
						24V RMS / 9.79A RMS

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: M=Magnet wire self-leads. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/- 10%
 RATED PRIMARY CURRENT: 4.31/2.16A

RATED FREQ.: 50/60 Hz
 TEMP RISE AT RATED LOAD = 64 °C

DIMENSIONS/WEIGHT:

OD = 5.3"
 H = 2.6"
 WEIGHT = 8.1 LBS.

MOUNTING:

WASHER/PADS = 110mm
 THICKNESS = 0.08"
 HOLE DIAMETER = 0.32"

CORE DATA:

CORE # 500
 NO-LOAD LOSS = 2.3 W
 NO-LOAD AMPS < 21.2 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66-1988.

SPEC DATE: 3/12/92	┌───┐	Label:	┌───┐
	(LOGO)	Transformer # 749.242	
		Prim. 2x117V 50/60Hz bk(wh-ye/or-bk)	
		Sec. 2x24V / 9.79A br-re/or-ye	
BY: _____	└───┘	(date code)	└───┘