

DATA SHEET FOR  
TRANSFORMER # 767.332

STANDARD

page 1 of 1

<u>LEADS</u>	<u>SCHEMATIC</u>				<u>LEADS</u>
M#17/8"    0V    WHITE	┌───┐		┌───┐	BROWN    0V	M#12/8"
M#17/8"    117V    YELLOW	┌───┐		┌───┐	RED $U_0 = 34.8V \text{ RMS}$ 33V RMS / 10.15A RMS	M#12/8"
M#17/8"    0V    ORANGE	┌───┐		┌───┐	ORANGE    0V	M#12/8"
M#17/8"    117V    BLACK	┌───┐		┌───┐	YELLOW $U_0 = 34.8V \text{ RMS}$ 33V RMS / 10.15A RMS	M#12/8"

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: M=Magnet wire self-leads. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/- 10%  
RATED PRIMARY CURRENT: 6.08/3.04A

RATED FREQ.: 50/60 Hz  
TEMP RISE AT RATED LOAD = 60 °C

DIMENSIONS/WEIGHT:  
OD = 6.3"  
H = 2.6"  
WEIGHT = 10.9 LBS.

MOUNTING:  
WASHER/PADS = 145mm  
THICKNESS = 0.08"  
HOLE DIAMETER = 0.40"

CORE DATA:  
CORE # 900664  
NO-LOAD LOSS = 3.1 W  
NO-LOAD AMPS < 28.6 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66-1988.

SPEC DATE: 3/12/92	┌───┐	Label:	┌───┐
BY: _____	(LOGO)	Transformer # 767.332 Prim. 2x117V 50/60Hz bk(wh-ye/or-bk) Sec. 2x33V / 10.15A br-re/or-ye (date code)	└───┘