

DATA SHEET FOR

TRANSFORMER # 767.382

STANDARD

page 1 of 1

<u>LEADS</u>			<u>SCHEMATIC</u>			<u>LEADS</u>		
M#17/8"	0V	WHITE	┌───┐		┌───┐	BROWN	0V	M#13/8"
M#17/8"	117V	YELLOW	┌───┐		┌───┐	RED	U ₀ = 40.1V RMS 38V RMS / 8.82A RMS	M#13/8"
M#17/8"	0V	ORANGE	┌───┐		┌───┐	ORANGE	0V	M#13/8"
M#17/8"	117V	BLACK	┌───┐		┌───┐	YELLOW	U ₀ = 40.1V RMS 38V RMS / 8.82A RMS	M#13/8"

PRIMARIES ARE INSIDE A SLEEVE.

Primaries must be connected together in series or in parallel.

LEADS: M=Magnet wire self-leads. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 117/234V +/- 10%
 RATED PRIMARY CURRENT: 6.10/3.05A

RATED FREQ.: 50/60 Hz
 TEMP RISE AT RATED LOAD = 64 °C

DIMENSIONS/WEIGHT:
 OD = 6.3"
 H = 2.6"
 WEIGHT = 10.9 LBS.

MOUNTING:
 WASHER/PADS = 145mm
 THICKNESS = 0.08"
 HOLE DIAMETER = 0.40"

CORE DATA:
 CORE # 900664
 NO-LOAD LOSS = 3.1 W
 NO-LOAD AMPS < 28.6 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66-1988.

SPEC DATE: 3/12/92		┌───┐	Label:			┌───┐
		(LOGO)		Transformer # 767.382		
		┌───┐		Prim. 2x117V 50/60Hz bk(wh-ye/or-bk)		
BY: _____		┌───┐		Sec. 2x38V / 8.82A br-re/or-ye		
		┌───┐		(date code)		