



DATA SHEET FOR
TRANSFORMER # U1509

Made for STANDARD

LEADS

SCHEMATIC

LEADS

S#14/8"	0V	WHITE		BLUE	0V	2xS#10/8"
	N/R THERMAL FUSE 121°C					UO = 12.2V RMS
S#14/8"	120V	BLACK		YELLOW	11.8V RMS / 750VA	2xS#10/8"

PRIMARIES ARE INSIDE A SLEEVE.

LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".

Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120V +/-10%
 RATED PRIMARY CURRENT: 6.51A
 RATED FREQUENCY: 60 Hz
 TEMP. RISE AT RATED LOAD: 45°C

DIMENSIONS/WEIGHT:

OD = 6.4"
H = 2.5"
WEIGHT = 12.6 LBS.

MOUNTING:

ONE WASHER/TWO PADS 145mm
THICKNESS = 0.08"
HOLE DIAMETER = 0.40"

CORE DATA:

CORE # 800
CORE LOSS = 3.5 W
NO-LOAD CURRENT = 71 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL506 and CUL certified to CSA C22.2 No. 66 standards. ROHS compliant. Class B insulation.

Label:



SPEC DATE: 02/06/15

Transformer # U15109
INPUT: 120V 60Hz
OUTPUT: 11.8V / 750W

WHT-BLK
BLU-YEL

(Logo)

By: **MX**

(date code)

TOROID CORPORATION