DATA SHEET FOR

TRANSFORMER # 104.515

Made for STANDARD

LEADS			SCHEMATIC		LEADS
S#22/8"	0V	WHITE	GREEN	0V UO = 10.5V RMS	M#19/8"
S#22/8"	117V	WHITE	GREEN	9.1V DC / 2.0A DC*	M#19/8"
			ORANGE	+19.5V DC / 0.30A DC* UO = 19.5V RMS	S#22/8"
			GRAY	0V	S#22/8"
			GRAY	0V UO = 19.5V RMS	S#22/8"
			ORANGE	-19.5V DC / 0.30V DC*	S#22/8"

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded Lead wire. M=Magnet wire self-leads. Length tolerence: +/-1/2".
Manufacturing tolerance is +/- 3%.
*DC data calculated after FWB and CTB rectifier with capacitor filter at NOMINAL voltage.

NOMINAL SUPPLY: 117V +/-10%
RATED FREQ.: 60 Hz
RATED PRIMARY CURRENT: 0.5A
TEMP RISE AT RATED LOAD = 60 C

DIMENSIONS/WEIGHT:
OD = 2.8"
H = 1.3"
WEIGHT = 1.1 LBS.

MOUNTING:
WASHER/PADS = 60 mm
THICKNESS = 0.05"
HOLE DIAMETER = 0.20"

CORE DATA:
CORE # 30
NO-LOAD LOSS = 0.2 W
NO-LOAD AMPS = 5 mA

Dimensions stated above are nominal. Tolerance is 10%

OTHER SPECIFICATIONS: Transformer is UL recognized to UL 1411 and CSA certified to CSA C22.2 No. 66.

Label:

SPEC DATE: 12/27/95

(LOGO)

BY:

Transformer # 104.515 (ZA85309-B)
Prim. 117V 60Hz bk+(wh-wh)
Sec. 8.6V/3.0A gn-gn
Sec. 2x16.2V/.52A or-gy/gy-or
(date code) (100433)