

DATA SHEET FOR
TRANSFORMER # U1503


Made for STANDARD

page 1 of 1

LEADS

SCHEMATIC

LEADS

S#20/8" 0V	WHITE		BLUE	0V		S#16/8"
	N/R THERMAL FUSE 121°C				UO = 12.9V RMS	
S#20/8" 120V	BLACK		YELLOW	11.8V RMS / 75VA		S#16/8"

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120V +/-10%
RATED PRIMARY CURRENT: 0.69A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 35°C


DIMENSIONS/WEIGHT:
OD = 3.5"
H = 1.5"
WEIGHT = 2.1 LBS.

MOUNTING:
ONE WASHER/TWO PADS 70mm
THICKNESS = 0.05"
HOLE DIAMETER = 0.25"

CORE DATA:
CORE # 900081
CORE LOSS = 0.5 W
NO-LOAD CURRENT = 11 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL506 and CUL certified to CSA C22.2 No. 66 standards. ROHS compliant. Class B insulation.

SPEC DATE: 12/17/20 By: <i>mx</i>	Label: (Logo) (date code)	 Transformer # U1503 INPUT: 120V 60Hz OUTPUT: 11.8V / 75W WHT-BLK BLU-YEL
--	---	---

TOROID CORPORATION