

DATA SHEET FOR
TRANSFORMER # U1504


Made for STANDARD

page 1 of 1

LEADS

SCHEMATIC

LEADS

S#20/8" 0V	WHITE		BLUE 0V		S#14/8"
N/R THERMAL FUSE 121°C				UO = 12.9V RMS	
S#20/8" 120V	BLACK		YELLOW 11.8V RMS / 100VA		S#14/8"

PRIMARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120V +/-10%
RATED PRIMARY CURRENT: 0.92A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 40°C


DIMENSIONS/WEIGHT:
OD = 3.7"
H = 1.6"
WEIGHT = 2.5 LBS.

MOUNTING:
ONE WASHER/TWO PADS 70mm
THICKNESS = 0.05"
HOLE DIAMETER = 0.25"

CORE DATA:
CORE # 900100
CORE LOSS = 0.6 W
NO-LOAD CURRENT = 12 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL506 and CUL certified to CSA C22.2 No. 66 standards. ROHS compliant. Class B insulation.

<p>Label:</p> <p>SPEC DATE: 12/17/20</p> <p>(Logo)</p> <p>By: <i>mx</i></p>	<p>Transformer # U1504</p> <p>INPUT: 120V 60Hz</p> <p>OUTPUT: 11.8V / 100W</p> <p>(date code)</p>	<p></p> <p>WHT-BLK</p> <p>BLU-YEL</p>
---	---	--

TOROID CORPORATION