DATA SHEET FOR

TRANSFORMER # U1505

Made for STANDARD

LEADS			SCHEMATIC			LEADS
S#20/8"	0V	WHITE		BLUE	0V	S#14/8"
N/R THERMAL FUSE 121°C					UO = 12.8V RMS	
S#20/8"	120V	BLACK		YELLOW	11.8V RMS / 125VA	S#14/8"

SECONDARIES ARE INSIDE A SLEEVE.
LEADS: S=Multistranded wire. Length tolerance: +/- 1/2".
Manufacturing tolerance is +/- 3%.

NOMINAL SUPPLY: 120V +/-10%
RATED PRIMARY CURRENT: 1.15A
RATED FREQUENCY: 60 Hz
TEMP. RISE AT RATED LOAD: 46°C

DIMENSIONS/WEIGHT:	MOUNTING:	CORE DATA:
OD = 3.9"	ONE WASHER/TWO PADS 70mm	CORE # 900115
H = 1.6"	THICKNESS = 0.05"	CORE LOSS = 0.7 W
WEIGHT = 2.8 LBS.	HOLE DIAMETER = 0.25"	NO-LOAD CURRENT = 15 mA

Dimensions stated above are nominal. Tolerance is 10%.

OTHER SPECIFICATIONS: Transformer is UL recognized to UL506 and CUL certified to CSA C22.2 No. 66 standards. ROHS compliant. Class B insulation.

Label:

Transformer # U1505
INPUT: 120V 60Hz WHT-BLK
OUTPUT: 11.8V / 125W BLU-YEL

SPEC DATE: 12/17/20

(Logo)

By: mx

(date code)

TOROID CORPORATION

2020 Northwood Drive * Salisbury, MD 21801 * Tel: 410-860-0300 * Fax: 410-860-0302
e-mail: sales@toroid.com * web: www.toroid.com